

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 November 2006 (02.11.2006)

PCT

(10) International Publication Number
WO 2006/115988 A3

(51) International Patent Classification:
B60J 1/20 (2006.01)

(21) International Application Number:
PCT/US2006/014906

(22) International Filing Date: 20 April 2006 (20.04.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/673,506 21 April 2005 (21.04.2005) US
60/762,329 26 January 2006 (26.01.2006) US

(71) Applicant and

(72) Inventor: DAYTON, Roderick [US/US]; 17212 Misty
Lake Drive, Strongsville, OH 44136 (US).

(74) Agent: YIRGA, John, A.; Tarolli, Sundheim, Covell &
Tummino LLP, 1300 East Ninth Street - Suite 1700, Cleve-
land, OH 44114-1501 (US).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,

GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV,
LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI,
NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG,
SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,
RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

— with international search report
— before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

(88) Date of publication of the international search report:
10 May 2007

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: VEHICLE AIR DAM SYSTEM



(57) Abstract: An air dam is made of flexible cells installed adjacent to one another so that the air dam is capable of installation in many deflecting configurations on a vehicle and can also deflect under impact. The air dam system may be capable of being deployed at higher speeds while being stowed under the frame of the truck when the truck is operating on rough road surfaces to reduce the potential for air dam damage. The air dam system can be actuated pneumatically and when deployed tends to reduce aerodynamic drag by altering the path of airflow under and/or immediately around a vehicle. Other methods of actuation such as hydraulic or mechanical components may also be used with the air dam system. Alternatively, the air dam cells may be stationary and include an inflated bladder and/or flexible sleeve mounted adjacent to one another on an air dam frame.